

HIGH PERFORMANCE AIR DRYER

DATA AND SPECIFICATIONS

Dryer Type: Heat-less Regenerative Desiccant

WEIGHTS AND DIMENSIONS

Height: 25-3/4" (65.40 cm)
with feet: 26-1/4" (66.75 cm)

Width: 16" (40.64 cm)

Depth: 5-1/4" (13.33 cm)
with feet: 7-1/2" (19.05 cm)

Weight: 54 lbs. (24.49 kg)

Inlet Connection: 1/2" O.D. (SMC push-in style)

Outlet Connection: 1/2" O.D. (SMC push-in style)

AIR INPUT REQUIREMENTS

Clean Dry Air (CDA)

Oil Content: 0.8 ppm or better

Filter Rating: 0.3 micron or better

Dewpoint: <10°C @ 6.2 BAR (90 PSIG)

Supply Pressure: 90 to 110 PSIG

Air Flow: 24 scfm

AIR OUTPUT PERFORMANCE

Dewpoint: <-70°C @ 6.2 BAR (90 PSIG)

Air Pressure: input pressure minus 8 PSIG

Air Flow: 20scfm

POWER REQUIREMENTS

Available Configurations:*

115v, 60Hz

230v, 50Hz

208 - 220v, 60Hz

* Power Requirements are specified at the time of your order. High Performance Air Dryers are equipped with the required line cord and plug.



Specifications:

High Performance Air Dryer

©Copyright - 2012, inTEST Thermal Solutions. These specifications are valid for the standard system and are subject to change without notice.

Applications requiring modifications to electrical, mechanical, or thermal characteristics should be discussed with inTEST Thermal Solutions for possible accommodation at additional cost.

P/N SL10690 rev.A

ISO 9001
Certified

